

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 October 2001 (04.10.2001)


PCT

(10) International Publication Number
WO 01/73998 A2

- (51) International Patent Classification⁷: **H04L** (74) Agents: **WINTERS, William, E.** et al.; Townsend And Townsend And Crew LLP, Two Embarcadero Center, 8th Floor, San Francisco, CA 94111-3834 (US).
- (21) International Application Number: **PCT/US01/08218**
- (22) International Filing Date: 14 March 2001 (14.03.2001) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 09/537,820 28 March 2000 (28.03.2000) US (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (for all designated States except US): **MON-GONET** [US/US]; 990 Columbus Street, Ground Floor, San Francisco, CA 94133-2310 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **HENRY, Matthew, K.** [US/US]; 3333 Divisadero Street, San Francisco, CA 94123 (US).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: FAX-TO-EMAIL AND EMAIL-TO-FAX COMMUNICATION SYSTEM AND METHOD



(57) Abstract: A facsimile/email communication system and method providing a user the ability to send emails from any standalone facsimile machine and providing a user the ability to logon to a centralized web server and send facsimiles to any standalone fax machine.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 October 2001 (04.10.2001)

PCT

(10) International Publication Number
WO 01/73998 A3

(51) International Patent Classification⁷: **B41B 15/00**

(21) International Application Number: PCT/US01/08218

(22) International Filing Date: 14 March 2001 (14.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/537,820 28 March 2000 (28.03.2000) US

(71) Applicant (for all designated States except US): **MON-GONET** [US/US]; 990 Columbus Street, Ground Floor, San Francisco, CA 94133-2310 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HENRY, Matthew, K.** [US/US]; 3333 Divisadero Street, San Francisco, CA 94123 (US).

(74) Agents: **WINTERS, William, E.** et al.; Townsend And Townsend And Crew LLP, Two Embarcadero Center, 8th Floor, San Francisco, CA 94111-3834 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
10 January 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FAX-TO-EMAIL AND EMAIL-TO-FAX COMMUNICATION SYSTEM AND METHOD



(57) Abstract: A facsimile/email communication system (5) and method provides a user with the ability to send emails from any standalone facsimile machine (2) and provides a user the ability to log on to a centralized web server (via 8) and send facsimiles to any standalone fax machine.

WO 01/73998 A3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US01/08218

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :B41B 15/00
US CL :358/1.15
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
U.S. : 358/1.15,402,407,440,448; 382/317; 379/100.01,100.06,100.07,100.08,100.15,100.17

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EAST
search terms: facsimile, email, download, web site, web address, web page, extract, URL, ad, advertisement

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,790,639 A (RANALLI et al.) 04 August 1998, col. 3, lines 21-24	4-9,14-21,27-39
X	US 5,848,413 A (WOLFF) 08 December 1998, col. 5, lines 11-19, 35- col. 6, line 62.	22-26
X,P --- Y,P	US 6,104,500 A (ALAM et al.) 15 August 2000, All	1-3 and 10-12 ----- 4-9,14-21 and 27-39
A	US 6,157,706 A (RACHELSON) 05 December 2000, col. 5, lines 33-62.	42-56

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
07 SEPTEMBER 2001

Date of mailing of the international search report
31 OCT 2001

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

Authorized officer
KIMBERLY A. WILLIAMS
Telephone No. (703) 305-4869

FAX-TO-EMAIL AND EMAIL-TO-FAX COMMUNICATION SYSTEM AND METHOD

COPYRIGHT NOTICE

5 A portion of the disclosure of this patent document contains material that is subject to copyright protection. The copyright owner has no objection to the xerographic reproduction by anyone of the patent document or the patent disclosure in exactly the form it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights.

BACKGROUND OF THE INVENTION

10 The present invention relates to a facsimile (fax)/electronic mail (email) communication system. More particularly, the present invention provides for, among other things, sending and/or receiving emails, web page downloads and faxes from any standalone fax machine. A web page is a file written in hypertext markup language (HTML) and which is stored on a web server. It may also refer to images that appear as part of the page when it is displayed by a web browser.

15 Fax images can be moved over the Internet by converting fax signals having a fax format to an email format (e.g. RFC-822). Once the conversion is completed, the email is then transferred over the Internet to the intended destination according to the Simple Mail Transfer Protocol (SMTP) or similar protocol. The Internet is the worldwide network of networks based on the TCP/IP (Transmission Control Protocol/ Protocol). Currently, there are various subscriber based service that permit a subscriber to send fax images over the Internet.

25 According to one type of service, offered by companies such as eFax, Jfax, CallWave and Telebot, a subscriber is provided with a unique telephone number. Any documents faxed to that number are converted to email format and transferred to the subscriber's email inbox. One drawback of this type of service is that it requires the subscriber to have a specific telephone number associated with their email address. A second drawback is that the subscriber must distribute the personal fax telephone number to any persons who would potentially want to send a fax to the subscriber. Finally, this type of service is expensive to operate from the service provider's perspective since the

30

WO 01/73998

costs associated with buying and operating so many individual and dedicated phone numbers is very high.

Another type of service is the service offered by UUNET, which requires a subscriber to attach additional hardware between the subscriber's fax machine and the service's network. The purpose of this service is to reduce long distance faxing costs for high volume users. The UUNET system converts a fax to the equivalent of an email and then routes the email over UUNET's network to the nearest UUFAX server. The UUFAX server converts the email back to fax format and transmits the fax using a local call to the fax machine at the destination. A drawback of this type of service is that it takes time and up-front hardware additions and expenditures to have access to the service.

SUMMARY OF THE INVENTION

Generally, the present invention comprises a facsimile/email communication system and method, whereby a user is able to send emails from any standalone facsimile machine and is also able to send facsimiles to any standalone fax machine, from either a centralized web server or a client machine connected to the Internet.

According to one aspect of the invention, a system for communicating an email from a facsimile is provided. An exemplary embodiment of this system comprises: a facsimile server configured to receive, from a start location, a facsimile in a facsimile image format, the facsimile including an email address; a character recognizer in communication with the facsimile server and configured to extract the email address; a first format converter configured to receive the facsimile and convert the facsimile to an email in an email format; an email server configured to receive the email and extracted email address and transmit the email to an end location identified by the email address; and an advertisement server configured to generate a confirmation page incorporating an advertisement on the confirmation page.

According to a second aspect of the invention, a method of communicating an email from a facsimile is provided. An exemplary embodiment of this method comprises the steps of: receiving a facsimile in a facsimile image format from a start location, the facsimile including an email address; extracting the email address from the facsimile; converting the facsimile image format to an email having an email format; and generating a confirmation page having an advertisement therein.

According to a third aspect of the invention, a system for communicating between facsimile and email is provided. An exemplary embodiment of this system comprises: a network operating center; and a plurality of geographically distributed points of presence in communication with the network operating center, each point of presence
5 having, a facsimile server configured to receive, from a start location, a facsimile in a facsimile image format, the facsimile including an email address; a character recognizer in communication with the facsimile server and configured to extract the email address; a first format converter configured to receive the facsimile and convert the facsimile to an email in an email format; an email server configured to receive the email and extracted
10 email address and transmit the email to an end location identified by the email address; and an advertisement server configured to generate a confirmation page incorporating an advertisement on the confirmation page.

According to a fourth aspect of the invention, a system for communicating a facsimile from an email is provided. An exemplary embodiment of this system
15 comprises: a network operating center having a web server to which a user can log on to over the Internet to compose an email, the web server configured to capture a facsimile number contained within the email; and a plurality of geographically distributed points of presence in communication with the network operating center, each point of presence having, an email server configured to receive the email in an email format; a first format
20 converter in communication with the email server and configured to convert it into a facsimile having a facsimile image format; an advertisement server having a return facsimile page composer and configured to generate a return facsimile page incorporating an advertisement; a second format converter configured to receive and convert the facsimile and return facsimile page to a facsimile encoded bitmap image; and a fax
25 spooler configured to receive the facsimile encoded bitmap image and transmit it to a destination identified by the facsimile number.

According to a fifth aspect of the invention, a method of communicating a facsimile from an email is provided. An exemplary embodiment of this method comprises the steps of: logging onto a web server of a network operating center;
30 composing an email having a facsimile number therein; capturing the facsimile number; converting the email to a facsimile; generating a return facsimile page; incorporating an advertisement in the return facsimile page; and sending the facsimile and return facsimile page to a destination identified by the facsimile number.

A further understanding of the nature and advantages of the inventions herein may be realized by reference to the remaining portions of the specification and the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 is a block diagram of the system, according to an exemplary embodiment of the present invention.

FIG. 2 is a block diagram showing a hardware configuration of a Point of Presence (POP) providing a fax/email interface according to an exemplary embodiment of the present invention.

10 FIG. 3A is an illustration of a process of obtaining an address page, according to an exemplary embodiment of the present invention.

FIG. 3B is an illustration of a process of a user interacting with the system of the present invention to send an email from a fax machine, according to an exemplary embodiment of the present invention.

15 FIG. 4 is an exemplary illustration of an address page received from the POP of FIG. 2.

FIG. 5 is a block diagram showing the software architecture of the POP of FIG. 2.

20 FIG. 6 is an exemplary illustration of a fax-to-email confirmation page received from the POP of FIG. 2.

FIG. 7 is a block diagram of a network operations center (NOC).

FIG. 8A is an illustration of a process of a user interacting with the system of the present invention to send a fax from an email, according to an exemplary embodiment of the present invention.

25 FIG. 8B is an illustration of a reply process wherein a recipient of the fax, delivered in the process according to FIG. 8A, replies to the fax using a return fax page.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

30 FIG. 1 is a high-level block diagram of a facsimile/email communication system 5 according to one embodiment of the present invention. System 5 comprises a network operations center (NOC) 8, selectively coupled to both the Plain Old Telephone System (POTS) and the Internet, and a plurality of Points of Presence (POPs) 10 selectively coupled to NOC 8 via the POTS and the Internet. The "Internet," as meant

here, means the worldwide network of networks based on the TCP/IP protocol and all means of access thereto (e.g. a local area network having an email system and being coupled to the Internet). (TCP/IP stands for "Transmission Control Protocol/ Protocol" and is a language governing communication between all computers on the Internet.)

5 As will be explained in detail below, system 5 permits a user to, among other things, send an e-mail from any standalone fax machine 2 and receive faxes from a fax or email sender without having to distribute a unique and predefined fax number to the fax or email sender. Here, it should be emphasized that the fax machine 2, as shown in FIG. 1, is only a working example. In other words fax machine as it is used in the
10 context of the present invention may also comprise any facsimile protocol compliant communication device. Similarly, computer workstation 4, in FIG. 1, is only a working example. In other words any device that is capable of sending an email may be used instead of computer workstation 4.

POPs 10 are distributed over a wide geographic area, for example, the
15 United States or throughout the world. An exemplary embodiment of a POP 10 is shown in FIG. 2. POP 10 comprises one or more fax modem banks 20; one or more fax servers 22; an advertisement and statistics (ad/stat) server 24; an email server 26; an interactive voice response (IVR) unit 28; an Ethernet switch 30; an IP router 32; and a T-1 channel service unit (CSU) 34. It should be emphasized that the embodiment of POP 10 in FIG. 2
20 is only exemplary. For example, other configurations are within the spirit and scope of the present invention, including but not limited to use of higher-capacity Internet access lines (e.g. T-3), provision for multiple switched email servers, etc. FIGS. 1 and 2 will be described in further detail in the context of the description presented below.

Referring now to FIG. 3A, there is shown an illustration of how a user
25 obtains an "address page" from a fax server 22, according to an exemplary embodiment of the present invention. At step 40, the user dials a specific toll-free (e.g. 1-800) fax-back number from any fax machine or telephone. This fax-back number is routed by the telephone network via the POTS to a POP 10, based on the user's geographic locale. As shown in FIG. 2, fax modem bank 20 of POP 10 receives the fax over, for example, a B-1
30 line, which comprises 24-line telephone bundle. Then, at step 42, POP 10 sends a blank email "address page" back to the user with further instructions on how to send an email from the user's fax machine.

The email address page looks like a normal fax cover sheet, but it contains lines of blank character boxes and a local telephone number the user can use so that the

WO 01/73998

fax can be sent without the user having to incur any cost. The local telephone number is generated by a table driven translation process through automatic number identification, detectable from outbound 1-800 numbers. In an alternative embodiment each POP 10 of system 5 would be accessible using a single toll-free number. An exemplary email address page is shown in FIG. 4. In one embodiment the character boxes 61 have "tickmarks" 63 on the edges of each character box 61. Tickmarks 63 have the effect of coercing the user to enter characters in the character boxes 61 but away from the character box edges. Characters entered away from the character box edges is beneficial, since later in the process, when character recognition is performed, the characters can be identified more accurately.

Referring now to FIG. 3B, there is shown an illustration of how a user interacts with the system 5 of the present invention to send an email from a fax machine, 2 according to an exemplary embodiment of the present invention. At step 44, the user fills in the letterboxes, in normal handwriting, with the final email address(es) it wishes to send to, e.g., "john_doe@generic.com". Alternatively, the email address can be printed in a machine-readable format. In an alternative embodiment, the email address page includes an "advanced features page," which can be downloaded to the user's fax so that the user can create a group distribution list.

At step 46, the user sends the fax to the local number of the selected POP 20 10, where it is received by a fax modem bank 20 on fax server 22. Fax modem bank 20 includes an incoming fax spooler 60, which converts the fax to an image file format, which may be, for example the standard G3 TIFF format and then temporarily stores the imaged fax in a spool area on a local disk drive (not shown in the figures). The imaged email address page is then transmitted to one of the fax servers 22 of POP 10 for further processing.

25 In addition to fax spooler 60, and as is shown in FIG. 5, the software architecture 70 for each fax server 22 comprises a front page (i.e. address page) character recognition module 62, a fax-to-email gateway 64, a email-to-fax gateway 66 and an outgoing fax spooler 68.

30 At step 48, front page character recognition module 62 operates to extract the imaged email address from the imaged email address page. Preferably, front page character recognition module 62 does this by optical character recognition (OCR).

At step 50, the electronic image of the fax is encapsulated and formatted into a MIME-compliant email message by fax-to-email gateway 64. "MIME" stands for

Multipurpose Internet Mail Extensions and refers to an official Internet standard that specifies how email messages must be formatted so that they can be exchanged between different email systems. The electronic image of the fax is then transmitted to email server 26 as an attachment to the email.

5 Upon receipt of the fax image by email server 26, email server 26 transmits the delivery status of the email to advertisement and statistics server (ad/stat server) 24. As shown in FIG. 5, the software architecture 71 of ad/stat server 24 comprises a confirmation and instruction page composer 72, a title page composer 74 and a PostScript rendering engine 76. Confirmation and instruction page composer 72
10 receives the delivery status of the email from email server 26 and subsequently generates delivery or non-delivery notifications and user instruction pages in PostScript format.

 At step 52, confirmation and instruction page composer 72 generates a confirmation and instruction page, and, at step 54, retrieves advertisements from ad/stat server 24 and incorporates the advertisements into the confirmation and instruction page.
15 Additionally, at step 56, confirmation and instruction page composer 72 retrieves advertisements from ad/stat server 24, which are incorporated, e.g. in banner format into the email. Preferably, the advertisements incorporated in the confirmation and instruction page are specifically targeted to the user's geographic locale. The system 5 determines the user's geographic locale from the user's fax number's prefix and area code and
20 advertisements are then targeted based on demographic data characteristic of the user's neighborhood, e.g., average income bracket. In an alternative embodiment, the email address confirmation page includes an electronic commerce aspect, wherein the user is provided with a "check box" on the confirmation and instruction page, which the user can check to indicate further interest in a particular advertising offer. An exemplary
25 embodiment of a confirmation and instruction page is shown in FIG. 6.

 In yet another alternative embodiment, a toll-based (e.g. 1-900) number is provided to the user at the beginning of the process, i.e., in lieu of step 10 in FIG. 3A, to provide a user with the option between the free advertising subsidized service described above or a pay-per-use service where the confirmation and instruction page does not
30 incorporate advertisements.

 After the confirmation and instruction page has been composed, it is rasterized into a fax encoded bitmap image by PostScript rendering engine 76 and then sent to fax server 22 where outgoing fax spooler 68 operates to store the rasterized confirmation and instruction page on a local disk drive for subsequent delivery. Because

WO 01/73998

bitmap image rendering is a computationally intensive process, a custom load-sharing software for distributing the rasterization process between a number of fax servers 22 machines may be employed as an alternative embodiment.

At steps 58, the email (with the advertisements) is sent over the Internet to the intended recipient using, for example, SMTP protocol, and as an attachment in a standard format, e.g. GIF file, viewable on the majority of platforms.

Finally, at step 59, the confirmation and instruction page is sent over the POTS to the user, the confirmation and instruction page incorporating an advertisement as explained above.

At this point, it should be emphasized that, whereas the software modules of the software architecture of FIG. 5 are shown to be distributed over multiple servers, one skilled in the art would understand that all the software modules could reside on a single server or on different servers than is shown in the embodiment of FIG. 5.

In an alternative embodiment, a user can interact with the system of the present invention to send a facsimile from any standalone facsimile machine to any other standalone facsimile machine. To do this, the user procures a "facsimile number page," as for example, similar to procuring the "email address page" described above in relation to steps 40 and 42. The user then enters a facsimile number of the intended facsimile recipient, for example, in handwritten format or printed machine readable format, and then faxes the facsimile to the local number of the selected POP 10 as in steps 44 and 46 described above (or, alternative, enters a pay-per-use toll-based number as is also described above). Upon receipt of the facsimile by the selected POP 10, the facsimile number is then extracted and the electronic image of the facsimile is formatted into a MIME-compliant email message by fax-to-email gateway 64, similar to steps 48 and 50 above. Next, email server 26 transmits the MIME image to an email-to-fax gateway 66, which could reside on a different POP 10, where the email-to-fax gateway 66 converts the MIME image into a text-formatted (e.g. PostScript) file. Then, PostScript rendering engine 96 operates to rasterize the text-formatted file into a fax encoded bit map image. And, finally, outgoing fax spooler 68 receives the fax encoded bit map image and transmits it to the intended facsimile recipient.

In yet another embodiment of the present invention, webpages can be downloaded via fax. In this embodiment, a user is provided with an "address page" as described above. This address page provides letterboxes for entering the desired web address (which, for example can be entered in normal handwriting or printed in a machine

readable format) and an indicator of some sort, which the user can use to request the number of pages from the web address the user wishes to download. One type of indicator on the address page, for example, could be a series of bubbles positioned at predetermined positions on the address page.

5 Referring now to FIG. 7, there is shown a network operations center (NOC) 8, according to an exemplary embodiment of the present invention. NOC 8 functions as the system headquarters and is configured to communicate with all POPs 10, as was shown and described in reference to FIG. 1. NOC 8 comprises an Internet access router and firewall component (IP router) 82 coupled between the Internet via, for
10 example, a T1 channel service unit (CSU) 84 and an Ethernet switch 86 (at a data rate of, for example, 100 Mbps); a web server 88 coupled to IP router 82; a private branch exchange (PBX) 90 coupled to the telephone network via, for example, a B-1 line; an interactive voice response (IVR) unit 92 coupled to PBX 90 and a computer-telephony integrated (CTI) server 94 coupled between IVR unit 92 and Ethernet switch 86. Also
15 coupled to Ethernet switch 86 is an NOC statistics server 96; an NOC advertisement statistics server 98; NOC workstations 100; and administrative/development workstations 102.

NOC advertisement statistics server 98 stores, and makes available to advertisers, statistics relating to the advertiser's advertisement(s), for example, the
20 number of times the advertisement was sent, the number of positive responses from viewers of the advertisement, etc.

NOC administrative/development workstations function as a help desk to those users who log on to web server 88 and also allow the system provider to do development, for example, improving the functionality of the web site provided by web
25 server 88.

IVR unit 92 permits a user to dial into the NOC via PBX 90 using the same 1-800 toll free access number used in the initiation of a fax-to-email process described above. IVR 92 provides user's with voice prompts, which the user can respond to using the telephone keypad. The prompts may relate to, for example, use instructions
30 or may permit a user to download information from the Internet, e.g. stock quotes, weather predictions, travel information, etc.

In another embodiment of the present invention, a user can logon to web server 88 from, for example, a computer workstation 4 (See FIG. 1), and then send a fax

WO 01/73998

from an email to any standalone fax machine. An exemplary process for accomplishing this is shown in FIG. 8A.

5 At step 110, after the user logs on to web server 88 (See FIG. 7), the user sends an email to web server 88. Then, at step 112, web server 88 captures and stores the user's email address and the fax number to which the user wishes to send the fax. This information is relayed over the Internet to email server 26 of the, preferably, nearest POP 10, to which the fax number is associated. As shown in FIG. 5, each email server 26 contains a mail transfer agent 39, which accepts the email from NOC 8. Email-to-fax gateway 66 then operates to convert the email message into PostScript text.

10 At step 114 title page composer 74 generates a return fax page, and, at step 116 retrieves advertisements from ad/stat server 24 and incorporates the advertisements into the return fax page. Preferably, the advertisements are specifically targeted to the fax recipient's location. The system 5 determines this from the recipient's fax number's prefix and area code by comparing the numbers to area code and prefix numbers stored in 15 ad/stat server 24. Once the neighborhood is identified, advertisements are then targeted based on demographic data characteristic of the recipient's neighborhood, e.g., average income bracket. In an alternative embodiment, the return fax page includes an electronic commerce aspect, wherein the fax recipient is provided with a "check box" on the return 20 fax page, which the recipient can check to indicate further interest in a particular advertising offer.

After the return fax page has been composed, it and the converted fax image are rasterized into a fax encoded bitmap image by PostScript rendering engine 76 and then sent to a fax modem bank 20 of POP 10 where outgoing fax spooler 68 operates to store the rasterized fax and return fax page on a local disk drive for subsequent 25 delivery.

At step 118, the fax and return fax page are sent over the POTS to the fax recipient.

Referring now to FIG. 8B, at step 120, upon receipt of the fax and return fax page, the fax recipient uses the return fax page to reply to the fax and sends the reply 30 fax at step 122.

At step 124, title page composer 74 of ad/stat server 24 operates to generate a confirmation page incorporating a second advertisement, which is then, at step 126, sent back to the return fax page user. Steps 124 and 126 substantially follow the steps 54 and 59 as described in reference to the fax-to-email process of FIG. 3B.

The advertising subsidized aspect of the system and method of the present invention also allows a user to send a fax from any standalone fax machine to any other standalone fax machine for free, thereby avoiding long distance telephone charges, which are typically billed for any long-distance fax transmission. To accomplish this, a user simply dials the toll free (1-800) access number, as explained above, to obtain a local number to a POP 10. Local POP 10 then responds by faxing back an address page to the user. Steps 44 through 48 are then performed, as was described in relation to FIG. 3B, followed by steps 110 through 118 as was described previously in relation to FIG. 8A. The only difference from the process as described above would be to provide letterboxes for fax addresses on the address page and provide for OCR capability for extracting fax addresses.

In another alternative embodiment of the present invention, NOC 8 includes a local database (not shown in FIG. 7), which is configured to store a frequent user's email address book. The user can logon to web server 88, upload the address book and associate nicknames or real names with each email address (e.g. "John Doe" for john_doe@generic.com). By doing this, the user can then send emails from any standalone fax machine simply by filling in the letterboxes of the address page (as described previously with respect to FIG. 3B) with the nickname or real name of the intended recipient.

Finally, in another exemplary embodiment of the present invention, advertisers are provided with a "dynamic print advertising" service, whereby an advertiser can logon to web server 88 of NOC 8, open an account, create advertisements and customize them based on specific demographic information.

In summary, the method and apparatus of the present invention permits a user to, among other things, send an e-mail from any standalone fax machine; receive a fax from another without requiring the user to have previously procured and distributed a unique and predefined fax number; and send a fax from an email by logging onto a web server provided by a centralized operating center.

Although the invention has been described in terms of preferred methods and structure, it will be obvious to those skilled in the art that many modifications and alterations may be made to the disclosed embodiments without departing from the invention. Hence, these modifications and alterations are intended to be considered as within the spirit and scope of the invention as defined by the appended claims.

WO 01/73998

WHAT IS CLAIMED IS:

- 1
2
3
4
5
6
7
8
9
10
11
12
1
2
1
2
3
1
2
3
1
2
3
1
2
3
1
2
3
1
2
3
1. A system for communicating an email to an email destination from a facsimile protocol compliant communication device, comprising:
a facsimile server configured to receive, from the facsimile protocol compliant communication device, a facsimile in a facsimile image format, the facsimile including a representation of an email address that references the email destination;
a character recognizer in communication with the facsimile server and configured to extract the email address from the facsimile;
a first format converter configured to receive the facsimile and convert the facsimile image format to an email format suitable for transport over an email system;
and
an email server configured to receive the email and extracted email address and transmit the email to the email destination.
2. The system of claim 1, wherein the facsimile protocol compliant communication device comprises a facsimile machine.
3. The system of claim 2, wherein the facsimile machine is configured to receive a hard copy of the facsimile, the hard copy having a cover page including the email address positioned at a predetermined location on the cover page.
4. The system of claim 1, further comprising an advertisement server in communication with the email server and configured to receive a delivery status from the email server.
5. The system of claim 4, wherein the advertisement server includes a confirmation page composer configured to generate a confirmation page.
6. The system of claim 5, wherein the confirmation page composer is configured to receive the delivery status and generate delivery and non-delivery notifications.
7. The system of claim 6, wherein the facsimile server is configured to receive the delivery and non-delivery notifications in facsimile format for transmission to the facsimile protocol compliant communication device.

1 8. The system of claim 5, wherein the confirmation page composer is
2 further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

1 9. The system of claim 8, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.

1 10. The system of claim 1, wherein the character recognizer extracts
2 the email address by optical character recognition.

1 11. The system of claim 1, wherein the email address is handwritten.

1 12. The system of claim 1, wherein the email address is printed in a
2 machine readable format.

1 13. The system of claim 1, wherein the advertisement server is further
2 configured to store advertising statistics.

1 14. A method of communicating an email to an email destination from
2 a facsimile protocol compliant communication device, the method comprising the steps
3 of:

4 receiving a facsimile in a facsimile image format from the facsimile
5 protocol compliant communication device, the facsimile including a representation of an
6 email address that references the email address;
7 extracting the email address from the facsimile;
8 converting the facsimile image format to an email format suitable for
9 transport over an email system; and
10 generating a confirmation page.

1 15. The method of claim 14, wherein the facsimile protocol compliant
2 communication device comprises a facsimile machine.

1 16. The method of claim 14, further comprising the step of requesting,
2 via the facsimile protocol compliant communication device, a facsimile cover page
3 having a predefined position for accepting the email address.

WO 01/73998

- 1 17. The method of claim 14, wherein the step of extracting is
2 performed by optical character recognition.
- 1 18. The method of claim 14, wherein the email address is handwritten.
- 1 19. The method of claim 14, wherein the email address is printed in a
2 machine readable format.
- 1 20. The method of claim 14, further comprising the step of
2 incorporating an advertisement on the confirmation page.
- 1 21. The method of claim 20, further comprising the step of delivering
2 the confirmation page to the facsimile protocol compliant communication device.
- 1 22. A method of downloading web pages from a web site to a facsimile
2 protocol compliant communication device, the method comprising the steps of:
3 receiving a facsimile in a facsimile image format from facsimile protocol
4 compliant communication device, the facsimile including a representation of a web site
5 address that references the web site and a number of pages to be downloaded from the
6 web site;
7 extracting the web site address from the facsimile;
8 connecting to the web site identified by the web site address;
9 downloading the pages from the web site;
10 converting the pages to a facsimile image format; and
11 transmitting the facsimile image formatted pages to the facsimile machine.
- 1 23. The method of claim 22, further comprising the step of requesting,
2 via the facsimile protocol compliant communication device, a facsimile cover page
3 having a predefined position for accepting the web site address.
- 1 24. The method of claim 22, wherein the step of extracting is
2 performed by optical character recognition.
- 1 25. The method of claim 22, wherein the web site address is
2 handwritten.

1 26. The method of claim 22, wherein the web site address is printed in
2 a machine readable format.

1 27. A system for communicating an email to an email destination from
2 a facsimile protocol compliant communication device, comprising:
3 a network operating center; and
4 a plurality of geographically distributed points of presence in
5 communication with the network operating center, each point of presence having,
6 a facsimile server configured to receive, from the facsimile
7 protocol compliant communication device, a facsimile in a facsimile image
8 format, the facsimile including a representation of an email address that references
9 the email destination;
10 a character recognizer in communication with the facsimile server
11 and configured to extract the email address from the facsimile;
12 a first format converter configured to receive the facsimile and
13 convert the facsimile to an email having a format suitable for transport over an
14 email system; and
15 an email server configured to receive the email and extracted email
16 address and transmit the email to the email destination.

1 28. The system of claim 27, wherein the facsimile protocol compliant
2 communication device comprises a facsimile machine.

1 29. The system of claim 27, wherein the facsimile protocol compliant
2 communication device is configured to receive a hard copy of the facsimile, the hard copy
3 having a cover page including the email address positioned at a predetermined location on
4 the cover page.

1 30. The system of claim 27, wherein the cover page is provided by the
2 network operating center via a toll-free telephone number.

1 31. The system of claim 27, wherein each point of presence includes an
2 advertisement server in communication with the associated email server and configured
3 to receive a delivery status from the email server.

WO 01/73998

1 32. The system of claim 31, wherein the advertisement server includes
2 a confirmation page composer configured to generate a confirmation page.

1 33. The system of claim 32, wherein the confirmation page composer
2 is configured to receive the delivery status and generate delivery and non-delivery
3 notifications.

1 34. The system of claim 33, wherein the facsimile server is configured
2 to receive the delivery and non-delivery notifications in facsimile format for transmission
3 to the facsimile protocol compliant communication device.

1 35. The system of claim 32, wherein the confirmation page composer
2 is further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

1 36. The system of claim 35, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.

1 37. The system of claim 27, wherein the character recognizer extracts
2 the email address by optical character recognition.

1 38. The system of claim 27, wherein the email address is handwritten.

1 39. The system of claim 27, wherein the email address is printed in a
2 machine readable format.

1 40. The system of claim 27, wherein the network operating center
2 further comprises:

3 an advertisement and statistics server in communication with the
4 advertisement servers of the points of presence and operable to store advertisements and
5 advertising statistics.

1 41. The system of claim 40, wherein the network operating center
2 further comprises voice interactive means for communicating with the advertisement and
3 statistics server using voice input.

1 42. A system for communicating a facsimile to a facsimile destination
2 from an email protocol compliant communication device, comprising:
3 a network operating center having a web server to which a user can log on
4 to over the Internet to compose an email, the web server configured to capture a
5 representation of a facsimile number contained within the email that references the
6 facsimile destination; and
7 a plurality of geographically distributed points of presence in
8 communication with the network operating center, each point of presence having,
9 an email server configured to receive the email in an email format;
10 a first format converter in communication with the email server and
11 configured to convert the email to a facsimile having a facsimile image format;
12 an advertisement server having a return facsimile page composer
13 and configured to generate a return facsimile page incorporating an advertisement;
14 a second format converter configured to receive and convert the
15 facsimile and return facsimile page to a facsimile encoded bitmap image; and
16 a facsimile server configured to receive the facsimile encoded bitmap
17 image and transmit it to the facsimile destination.

1 43. The system of claim 42, wherein the network operating center,
2 further comprises:
3 a database in communication with the web server to which the user can
4 upload an address book having a list of names and associated facsimile numbers.

1 44. The system of claim 42, wherein the network operating center
2 further comprises:
3 an advertisement and statistics server in communication with the web
4 server, the web server further configured to permit an advertiser to open an account and
5 upload advertisements to the advertisement and statistics server.

1 45. The system of claim 44, wherein the network operating center
2 further comprises:
3 interactive voice response means for communicating with the
4 advertisement and statistics server and the web server.

WO 01/73998

1 46. A method of communicating a facsimile to a facsimile destination
2 from an email input, comprising the steps of:
3 logging onto a web server of a network operating center;
4 composing an email including a representation of a facsimile number that
5 references the facsimile destination;
6 capturing the facsimile number;
7 converting the email to a facsimile;
8 generating a return facsimile page;
9 incorporating an advertisement in the return facsimile page; and
10 sending the facsimile and return facsimile page to the facsimile
11 destination.

1 47. A system for communicating a facsimile to a facsimile destination
2 from a facsimile protocol compliant communication device, comprising:
3 a facsimile server configured to receive, from the facsimile protocol
4 compliant communication device, a facsimile in a facsimile image format, the facsimile
5 including a representation of a facsimile number that references the facsimile destination;
6 a character recognizer in communication with the facsimile server and
7 configured to extract the facsimile number from the facsimile;
8 a first format converter configured to receive the facsimile and convert the
9 facsimile image format to an email format suitable for transport over an email system;
10 an email server configured to receive the email and extracted facsimile
11 number;
12 a second format converter in communication with the email server and
13 configured to receive the email and convert it to a facsimile image having a facsimile
14 image format.

1 48. The system of claim 47, further comprising an advertisement server
2 in communication with the email server and configured to receive a delivery status from
3 the email server.

1 49. The system of claim 48, wherein the advertisement server includes
2 a confirmation page composer configured to generate a confirmation page.

1 50. The system of claim 49, wherein the confirmation page composer
2 is configured to receive the delivery status and generate delivery and non-delivery
3 notifications.

1 51. The system of claim 50, wherein the facsimile server is configured
2 to receive the delivery and non-delivery notifications in facsimile format for transmission
3 to the facsimile protocol compliant communication device.

1 52. The system of claim 49, wherein the confirmation page composer
2 is further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

1 53. The system of claim 52, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.

1 54. The system of claim 47, wherein the character recognizer extracts
2 the facsimile number by optical character recognition.

1 55. The system of claim 47, wherein the facsimile number is
2 handwritten.

1 56. The system of claim 47, wherein the facsimile number is printed in
2 a machine readable format.




FIG. 1.

AMENDED CLAIMS

[received by the International Bureau on 27 December 2001 (27.12.01);
original claims 1-56 replaced by amended claims 1-52; (8 pages)]

1 1. A system for communicating an email to an email destination from
2 a facsimile protocol compliant communication device, comprising:

3 a facsimile server configured to receive, from the facsimile protocol
4 compliant communication device, a facsimile in a facsimile image format, the facsimile
5 including an email address corresponding to the email destination;

6 a character recognizer in communication with the facsimile server and
7 configured to extract the email address from the facsimile;

8 a first format converter configured to receive the facsimile and convert the
9 facsimile image format to an email format suitable for transport over an email system;
10 and

11 an email server configured to receive the email and extracted email
12 address and transmit the email to the email destination.

1 2. The system of claim 1, wherein the facsimile protocol compliant
2 communication device comprises a facsimile machine.

1 3. The system of claim 2, wherein the facsimile machine is
2 configured to receive a hard copy of the facsimile, the hard copy having a cover page
3 including the email address positioned at a predetermined location on the cover page.

1 4. The system of claim 1, further comprising an advertisement server
2 in communication with the email server and configured to receive a delivery status from
3 the email server.

1 5. The system of claim 4, wherein the advertisement server includes a
2 confirmation page composer configured to generate a confirmation page having the
3 facsimile image format.

1 6. The system of claim 5, wherein the confirmation page composer is
2 configured to receive the delivery status and generate delivery and non-delivery
3 notifications.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(10) International Publication Number
WO 01/73998 A3

(43) International Publication Date
4 October 2001 (04.10.2001)

PCT

(51) International Patent Classification⁷: **B41B 15/00**

(21) International Application Number: **PCT/US01/08218**

(22) International Filing Date: 14 March 2001 (14.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 28 March 2000 (28.03.2000) US
09/537,820

(71) Applicant (for all designated States except US): **MON-
GONET [US/US]**; 990 Columbus Street, Ground Floor,
San Francisco, CA 94133-2310 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HENRY, Matthew,
K. [US/US]**; 3333 Divisadero Street, San Francisco, CA
94123 (US).

(74) Agents: **WINTERS, William, E. et al.**; Townsend And
Townsend And Crew LLP, Two Embarcadero Center, 8th
Floor, San Francisco, CA 94111-3834 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,
TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:
— with international search report
— with amended claims

(88) Date of publication of the international search report:
10 January 2002

Date of publication of the amended claims: 10 May 2002

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **FAX-TO-EMAIL AND EMAIL-TO-FAX COMMUNICATION SYSTEM AND METHOD**



(57) Abstract: A facsimile/email communication system (5) and method provides a user with the ability to send emails from any standalone facsimile machine (2) and provides a user the ability to log on to a centralized web server (via 8) and send facsimiles to any standalone fax machine

WO 01/73998 A3

1 7. The system of claim 6, wherein the facsimile server is configured
2 to receive the delivery and non-delivery notifications in facsimile format for transmission
3 to the facsimile protocol compliant communication device.

1 8. The system of claim 5, wherein the confirmation page composer is
2 further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

1 9. The system of claim 8, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.

1 10. The system of claim 1, wherein the character recognizer extracts
2 the email address by optical character recognition.

1 11. The system of claim 1, wherein the email address is handwritten.

1 12. The system of claim 1, wherein the email address is printed in a
2 machine readable format.

1 13. The system of claim 4, wherein the advertisement server is further
2 configured to store advertising statistics.

1 14. A method of communicating an email to an email destination from
2 a facsimile protocol compliant communication device, the method comprising the steps
3 of:

4 sending a facsimile in a facsimile image format from the facsimile
5 protocol compliant communication device to a remote operating center, the facsimile
6 including an email address corresponding to the email destination;

7 extracting the email address from the facsimile;

8 converting the facsimile image format to an email format suitable for
9 transport over an email system to the email destination; and

10 generating a confirmation page in the facsimile image format, at the
11 remote operating center, and sending the confirmation page to the facsimile protocol
12 compliant communication device.

WO 01/73998

- 1 15. The method of claim 14, wherein the facsimile protocol compliant
2 communication device comprises a facsimile machine.
- 1 16. The method of claim 14, wherein the facsimile includes a cover
2 page having the email address positioned at a predetermined location on the cover page.
- 1 17. The method of claim 16, further comprising, prior to the step of
2 sending, a step of receiving, by the facsimile protocol compliant communication device,
3 and from the remote operating center, the facsimile cover page.
- 1 18. The method of claim 14, wherein the step of extracting is
2 performed by optical character recognition.
- 1 19. The method of claim 14, wherein the email address is handwritten.
- 1 20. The method of claim 14, wherein the email address is printed in a
2 machine readable format.
- 1 21. The method of claim 14, further comprising the step of
2 incorporating an advertisement on the confirmation page.
- 1 22. The method of claim 21, further comprising the step of delivering
2 the confirmation page to the facsimile protocol compliant communication device.
- 1 23. A system for communicating an email to an email destination from
2 a facsimile protocol compliant communication device, comprising:
3 a network operating center; and
4 a plurality of geographically distributed points of presence having,
5 a facsimile server configured to receive, from the facsimile
6 protocol compliant communication device, a facsimile in a facsimile image
7 format, the facsimile including an email address corresponding to the email
8 destination;
9 a character recognizer in communication with the facsimile server
10 and configured to extract the email address from the facsimile;

11 a first format converter configured to receive the facsimile and
12 convert the facsimile to an email having a format suitable for transport over an
13 email system; and
14 an email server configured to receive the email and extracted email
15 address and transmit the email to the email destination.

1 24. The system of claim 23, wherein the facsimile protocol compliant
2 communication device comprises a facsimile machine.

1 25. The system of claim 23, wherein the facsimile protocol compliant
2 communication device is configured to receive a hard copy of the facsimile, the hard copy
3 having a cover page including the email address positioned at a predetermined location on
4 the cover page.

1 26. The system of claim 25, wherein the cover page is provided by the
2 network operating center via a toll-free telephone number.

1 27. The system of claim 23, wherein each point of presence includes an
2 advertisement server in communication with the associated email server and configured
3 to receive a delivery status from the email server.

1 28. The system of claim 27, wherein the advertisement server includes
2 a confirmation page composer configured to generate a confirmation page.

1 29. The system of claim 28, wherein the confirmation page composer
2 is configured to receive the delivery status and generate delivery and non-delivery
3 notifications.

1 30. The system of claim 29, wherein the facsimile server is configured
2 to receive the delivery and non-delivery notifications in facsimile format for transmission
3 to the facsimile protocol compliant communication device.

1 31. The system of claim 28, wherein the confirmation page composer
2 is further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

WO 01/73998

1 32. The system of claim 31, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.

1 33. The system of claim 23, wherein the character recognizer extracts
2 the email address by optical character recognition.

1 34. The system of claim 23, wherein the email address is handwritten.

1 35. The system of claim 23, wherein the email address is printed in a
2 machine readable format.

1 36. The system of claim 23, wherein the network operating center
2 further comprises:
3 an advertisement and statistics server in communication with the
4 advertisement servers of the points of presence and operable to store advertisements and
5 advertising statistics.

1 37. The system of claim 36, wherein the network operating center
2 further comprises voice interactive means for communicating with the advertisement and
3 statistics server using voice input.

1 38. A system for communicating a facsimile to a facsimile destination
2 from an email protocol compliant communication device, comprising:
3 a network operating center having a web server to which a user can log on
4 to over the Internet to compose an email, the web server configured to capture a
5 representation of a facsimile number contained within the email that references the
6 facsimile destination; and
7 a plurality of geographically distributed points of presence in
8 communication with the network operating center, each point of presence having,
9 an email server configured to receive the email in an email format;
10 a first format converter in communication with the email server and
11 configured to convert the email to a facsimile having a facsimile image format;
12 an advertisement server having a return facsimile page composer
13 and configured to generate a return facsimile page incorporating an advertisement;

14 a second format converter configured to receive and convert the
15 facsimile and return facsimile page to a facsimile encoded bitmap image; and
16 a facsimile server configured to receive the facsimile encoded bitmap
17 image and transmit it to the facsimile destination.

1 39. The system of claim 38, wherein the network operating center,
2 further comprises:

3 a database in communication with the web server to which the user can
4 upload an address book having a list of names and associated facsimile numbers.

1 40. The system of claim 38, wherein the network operating center
2 further comprises:
3 an advertisement and statistics server in communication with the web
4 server, the web server further configured to permit an advertiser to open an account and
5 upload advertisements to the advertisement and statistics server.

1 41. The system of claim 40, wherein the network operating center
2 further comprises:
3 interactive voice response means for communicating with the
4 advertisement and statistics server and the web server.

1 42. A method of communicating a facsimile to a facsimile destination
2 from an email input, comprising the steps of:
3 logging onto a web server of a network operating center;
4 composing an email including a representation of a facsimile number that
5 references the facsimile destination;
6 capturing the facsimile number;
7 converting the email to a facsimile;
8 generating a return facsimile page;
9 incorporating an advertisement in the return facsimile page; and
10 sending the facsimile and return facsimile page to the facsimile
11 destination.

1 43. A system for communicating a facsimile to a facsimile destination
2 from a facsimile protocol compliant communication device, comprising:

WO 01/73998

3 a facsimile server configured to receive, from the facsimile protocol
4 compliant communication device, a facsimile in a facsimile image format, the facsimile
5 including a representation of a facsimile number that references the facsimile destination;

6 a character recognizer in communication with the facsimile server and
7 configured to extract the facsimile number from the facsimile;

8 a first format converter configured to receive the facsimile and convert the
9 facsimile image format to an email format suitable for transport over an email system;

10 an email server configured to receive the email and extracted facsimile
11 number;

12 a second format converter in communication with the email server and
13 configured to receive the email and convert it to a facsimile image having a facsimile
14 image format.

1 44. The system of claim 43, further comprising an advertisement server
2 in communication with the email server and configured to receive a delivery status from
3 the email server.


1 45. The system of claim 44, wherein the advertisement server includes
2 a confirmation page composer configured to generate a confirmation page.

1 46. The system of claim 45, wherein the confirmation page composer
2 is configured to receive the delivery status and generate delivery and non-delivery
3 notifications.



1 47. The system of claim 46, wherein the facsimile server is configured
2 to receive the delivery and non-delivery notifications in facsimile format for transmission
3 to the facsimile protocol compliant communication device.

1 48. The system of claim 45, wherein the confirmation page composer
2 is further configured to retrieve an advertisement from the advertisement server and
3 incorporate the advertisement on the confirmation page.

1 49. The system of claim 48, wherein the facsimile server is configured
2 to receive the confirmation page in facsimile format for transmission to the facsimile
3 protocol compliant communication device.



3/8

**FIG. 3A.****FIG. 3B.**

4/8

Mongo Net

Send E-mail from a fax machine

free service from MongoNet

- * Fill in e-mail address(s) in the boxes below
- * Use this page as your fax cover sheet
- * Fax for free to 1(800)345-8765

Use capital (uppercase) letters. Handprint each letter, number and symbol as in the sample below:

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
V	W	X	Y	Z	1	2	3	4	5	6	7	8	9	0	@	_	-	.	#	

To: (Write e-mail address here, keep each letter in the center of the box and use dark ink)

@																				

Cc: (optional second e-mail address)


@																				

Cc: (optional third e-mail address)

@																				

Freehand Notes and Drawings:

GET:



Sponsor

Traffic and weather ☐

map ☐ movies ☐ restaurants ☐ stocks ☐ news ☐

Disclaimer: blah-blah-blah. Blah blah. Blah blah.
ah. Blah Blah. Blah. Blahblahblah.



FIG. 4.




FIG. 5.

6/8

MongoFax Confirmation Page:

Your transmission was sent to the following e-mail address(s) or fax number(s)

E-Mail: john_doe@generic.com

E-Mail: jane_doe@generic.com

Fax #: (415) 555.5555

If any of these addresses or fax numbers are incorrect,
please carefully fill out a new e-mail
address page and re-send.

Tear along dotted line.

Tear along dotted line.

Advertisement

Dream Vacations


**Presents the chance to enter to win a free, 14 day sailing
trip in the British Virgin Islands! Just fax back this
request with your name and phone number indicated
below, or take this coupon into a local travel agent.**

☐ Check this box if you would like to be entered to win.

Fax Back to: (xxx) xxx-xxxx

Name: _____

Telephone: _____



Your personal ID code is: 78W9ZST

FIG. 6.






FIG. 7.

**FIG. 8A.****FIG. 8B.**

THIS PAGE BLANK (USPTO)